







PD20 Flashlight

Fenix PD20 is a high-tech tool that is perfect for any lighting application with optimized design for focus and anti-rolling. It features six settings, 4 of them being output levels. This flexibility not only allows the user to select the best compromise between brightness and runtime for any given task but also has ability to aid in an emergency. The PD20 does all these and still retains an incredibly compact size. If you're looking for solid reliability, digitally regulated brightness, and compact size, this Fenix is for you.

Technical Parameters

ANSI/FSC	Turbo Mode		General Mode			
	Turbo	Strobe	Low	Mid	High	SOS
 OUTPUT	180 LUMENS	180 LUMENS	9 LUMENS	38 LUMENS	90 LUMENS	90 LUMENS
 RUNTIME	1h 41min		66h	10h	3h 56min	
 DISTANCE	102m					
 INTENSITY	2579cd					
 IMPACT RESISTANT	1.5m					
 WATERPROOF	IPX-8, underwater 2m					
EXTRA FUNCTION						
ACCESSORIES	holster, lanyard, body clip, two spare o-rings, and a rubber switch boot					

© Cree XP-G LED (R5) with a lifespan of 50,000 hours

© Uses one 3V CR123A battery (Lithium)

© 78.5mm (Length) x 22.2mm (Diameter)

- ◎ 39-gram weight (excluding batteries)
- ◎ Digitally regulated output-maintains constant brightness
- ◎ Patented structure avoids circuit damaging from reverse connection of battery
- ◎ Push-button tail cap switch
- ◎ Capable of standing up securely on a flat surface to serve as a candle
- ◎ Made of durable aircraft-grade aluminum
- ◎ Premium Type III hard-anodized anti-abrasive finish
- ◎ Toughened ultra-clear glass lens with anti-reflective coating

Notice: The above-mentioned parameters (tested with high-quality CR123A Lithium batteries in Lab) are approximate and may vary between flashlights, batteries, and environments.

Operation Instruction

Fully press (click) to switch on and turn the bezel to select the General Mode or the Turbo Mode. A soft-press (no click) anytime while the light is on will change the brightness levels of a certain mode. Keep the light off for over 2 seconds and the light will turn completely off, restoring the regulation circuit to the default setting.

Notice: The video for operating the flashlight, you can watch or download from our official website: www.fenixlight.com ->Service->Light operation video.

Battery Replacement

Unscrew the tail cap to insert the batteries with the anode side (+) toward the lights head, screw the tail cap back on to test.

Usage and Maintenance

- ◎ Please don't disassemble the sealed head, doing so can cause damage to the flashlight and will void the warranty.
- ◎ Please use battery of high quality, and take out the battery if the flashlight will not be used for a long time, or it may cause damage from electrolyte leakage or battery explosion.
- ◎ The o-ring may be worn out after using for a long time. If it happens, please replace the o-ring with a new one to keep the flashlight properly sealed against water.
- ◎ Please clean the contacts of your light from time to time, especially if the light flickers or doesn't light up. There may be several reasons for a flickering or not working light:

Reason A: The battery needs replacing.

Solution: Replace batteries (Please confirm the correct installation of anode and cathode).

Reason B: The threads, PCB board contact or other contacts are dirty.

Solution: Clean the contact points with an alcohol soaked cotton swab.

If the above methods don't work, please contact the distributors and refer to the warranty policy.

Product Warranty

We will replace products afflicted with manufacturing defects within 15 days of purchase and

repair a light free of charge within 24 months of purchase if problems develop with normal use; if repair is required after 24 months from the date of purchase, we will charge for parts. The total repair fee is dictated by the cost of the replaced materials.

Warranty Card Registration

We kindly suggest that you register your guarantee card on the official website for Fenixlight Limited. You can get an extra six-month warranty period once you have successfully registered. What's more, you could take part in the lottery of questionnaire at the same time.

Warning

The PD20 is a high-intensity lighting device and capable of causing eye damage, please avoid shining the light directly into the eyes.

Avoid the use of 16340 rechargeable Lithium batteries or damage will be caused to the light circuit.

FENIXLIGHT LIMITED

Tel: +86-755-29631163/83/93 Fax: +86-755-29631181

<http://www.fenixlight.com>

E-mail: info@fenixlight.com

Address: 8/F, 2nd Building, Dong Fang Ming

Industrial Center, 33rd District, Bao' an,

Shenzhen 518133, China