



Synthetic Multi-Purpose Grease

AMSOIL Synthetic Multi-Purpose Grease is qualified against the highest grease standards and designed for multiple-use applications. Composed of premium-quality synthetic base oils and calcium sulfonate complex thickeners, Multi-Purpose Grease provides exceptional film strength, shear resistance, adhesion properties and mechanical stability. It excels in temperature extremes by providing excellent oxidation stability, high-temperature dropping point and low-temperature torque value and pumping capability. AMSOIL Synthetic Multi-Purpose Grease is formulated with oil soluble extreme-pressure additives for heavy loads, as well as oxidation and corrosion inhibitors.

Performance Features

- Resists thermal and oxidation degradation
- Excellent water-washout resistance
- Outstanding low-temperature pumpability and torque value
- Adhesive and shear stable to prevent squeeze out
- Excellent load-carrying and EP performance

Application Recommendation

AMSOIL Synthetic Multi-Purpose Grease is the preferred choice for medium to high ambient temperatures, sleeve-type bushings, high shock-loading environments, wet environments and wheel bearings and other automotive applications.

AMSOIL Synthetic Multi-Purpose Grease is recommended in heavy- and light-duty applications found in manufacturing facilities, automobiles, agricultural and construction equipment. These include, but are not limited to, roller bearings, plain bearings, thrust bearings, gears, electric motors, presses, winches, bushings, wheel bearings, chassis lubrication, universal joints, ball joints, tie-rod ends and steering knuckles.

Compatibility

AMSOIL Synthetic Multi-Purpose Grease is compatible with many other types of greases. However, it is recommended that when changing greases, the equipment be cleaned of the old grease when possible or flushed with a liberal amount of Multi-Purpose Grease while the mechanism is in operation. Closely monitor the system for any inconsistencies. Grease compatibility questions should be referred to your AMSOIL representative or AMSOIL INC.



NLGI #2

TYPICAL TECHNICAL PROPERTIES**Synthetic Multi-Purpose Grease (GLC)**

	GLC	NLGI GC-LB Requirements
Thickener	calcium sulfonate complex	NR
NLGI consistency grade	2	NR
NLGI performance grade	GC-LB	NR
Penetration (ASTM D-217) (25°C [77°F], 0.1 mm)		
worked 60 strokes	282	220-340 min
Dropping point °F (°C) (ASTM D-2265)	>540 (>282)	428 (220) min
High temperature life, hours (ASTM D-3527)	120	80 min
Water washout, percent (ASTM D-1264)	1.70	15 max
Rust and corrosion (ASTM D-1743)	pass	pass
Oil separation, percent loss (ASTM D-1742)		
(24 hours, 25°C [77°F])	0	6.0 max
Leakage, g lost (ASTM D-4290)	4.2	10 max
Four-ball wear test, mm scar (ASTM D-2266)	0.40	0.60 max
Fretting wear, mg (ASTM D-4170)	2.3	10 max
Four-ball EP, kgf (ASTM D-2596)		
Weld point	620	200 min
Load wear index	74	30 min
Timken OK load test, lbs (ASTM D-2509)	70	NR
Low-temperature torque, N•m (ASTM D-4693)		
(-40°C [-40°F])	6.4	15.5 max
Oil viscosity		
40°C (104°F), cSt	165	NR
Color	red	NR
Texture	smooth with tack	NR

NR: not required for NLGI GC-LB labeling

APPLICATION MAINTENANCE

Maintaining a clean work environment is important when equipment greasing is performed. Wipe grease fittings clean prior to injecting grease to prevent contaminant ingestion. Maintain bearing housings one-third to one-half full of grease. Do not over-grease, as excessive heat buildup can result. Supplement standard grease maintenance by periodically cleaning and packing housings with fresh grease on an established maintenance schedule.

AMSOIL PRODUCT AVAILABILITY

AMSOIL Synthetic Multi-Purpose Grease is available in 3-oz. cartridges, 14-oz. cartridges, 35-lb. lugs, 120-lb. kegs, 400-lb. drums and in a 3 oz. cartridge grease gun kit.



AMSOIL products and Dealership information are available from your local AMSOIL Dealer.

Brian Klinkner - Direct Jobber #1642716

Ordering 800-985-5823 <http://www.BuyOil.co>