



ARE-C2+

Four channels smart battery charger

Compatible with
different battery types





ARE-C2+

Four channels smart battery charger

Fenix ARE-C2+ is a four channels smart charger, which is compatible with different types of Li-ion and Ni-MH/Ni-Cd batteries. High definition LCD screen displays charging status and battery level clearly. In addition, a car charging mode offers high convenience for users.



ARE-C2+

Four channels smart battery charger

- ✦ Compatible with different battery types
- ✦ LCD screen for charging display
- ✦ Supports AC and DC charging
- ✦ Built-in multi-protection circuit

ARE-C2+

Four channels smart battery charger



Compatible with
following battery types

- ✦ Li-ion: 26650, 18650, 16340, 14500, 10440
- ✦ Ni-MH / Ni-Cd: AA, AAA, C

ARE-C2+

Four channels smart battery charger



LCD screen for charging display

- ✦ After connecting to the power supply, the LCD screen will display the inserted battery types and voltages, and battery level will be displayed through battery status bar.
- ✦ The four channels are separately controlled by the four buttons.
- ✦ Single click the button, the screen will cycle through battery voltage→charging current→charging time. Long press any button to turn off the LCD screen. Single click the button will turn on the LCD screen again.

Note: Battery levels will not be displayed without power supply connected.



ARE-C2+

Four channels smart battery charger



Supports AC and DC charging

(Car adapter sold separately)

ARE-C2+

Four channels smart battery charger



Built-in multi -protection circuit

Ensures your safety and the quality in use of the battery.

ARE-C2+

Four channels smart battery charger



Specification parameters

- ✦ Input: AC100-240V/50-60Hz/0.35A (max) or DC12-24V/1A (max)
- ✦ Output: 4.2V, 1.0A: 18650, 26650, 16340, 14500, 10440 Li-ion battery
1.5V, 1.0A: AA, AAA, C Ni-MH / Ni-Cd battery
- ✦ Rated output power: 6W (Ni-MH/ Ni-Cd), 16.8W (Li-ion)
- ✦ Size: 145×75×38.5mm (length*width*height)
- ✦ Weight: 276.5g (excluding charging cable)
- ✦ Operating Temperature: -20°C to 50°C
- ✦ Operating Humidity: 5% to 90%
- ✦ Storage Temperature: -20°C to 85°C

ARE-C2+

Four channels smart battery charger



Included in the package:

- ✦ 1*ARE-C2+ battery charger
- ✦ 1*AC charging cable
- ✦ 1*User manual

Size: 235*152*94mm / 9.25*5.98*3.7in.

Gross weight: 400g / 14.11oz