

# UPGRADED Fan Delay Board

MARCH 2009



## Replaces "Thermal" Time Delays

OFF Delay Purges Air Ducts Of Residual Air

Increasing Efficiency



**R60B**

### SPECIFICATIONS:

#### INPUT

- \* Voltage: 18-30 VAC
- \* Frequency: 50-60 Hz

#### OUTPUT RATINGS

- \* Type: Relay
- \* N.O. contact: 20 amps resistive
- \* N.C. contact: 10 amps resistive

#### OFF TIME DELAY OPTIONS

- \* R60B- 30: 30 seconds
- \* R60B- 45: 45 seconds
- \* R60B- 60: 60 seconds

**LOW COMPETITIVE  
PRICE**

**OPEN BOARD  
FAN BLOWER CONTROL**

Controls the circulating fan  
in a heat pump, A/C and  
forced air systems

OFF delay purges ducts for  
residual air efficiency

Screw in terminals for R, C  
and G inputs

Blank quick connects for  
unused fan speed wires

**COMPACT SIZE**

**2 1/2" X 2 1/2"**

**OEM CUSTOM**

**OPTIONS AVAILABLE**

# VTRONIX

'A name you can trust'  
WWW.VTRONIX.COM

**Phone: 305-471-7600**

Fax: 305-471-9787

E-mail:  
**sales@vtronix.com**

318 Indian Trace #327  
Weston, Florida 33326  
USA